

SHARPSHOOTER

TOOLS FOR SUCCESS

CM[®] HTP & HTG PLAIN & GEARED CLEVIS TROLLEY

HTP & HTG | PLAIN & GEARED TYPE TROLLEY

The CM HTP and HTG Clevis Trolley can easily be installed in seconds for the exact positioning or seamless traversing of loads. This universal trolley is compatible with nearly any Columbus McKinnon hoist brand or model.

QUICK, SIMPLE INSTALLATION IN SECONDS

Adjust the flange width in a matter of seconds by turning the trolley axle, eliminating the need for loose parts, including spacer washers, when installing the trolley.

A TRULY UNIVERSAL TROLLEY

The HTP and HTG Clevis Trolleys are compatible with nearly any CMCO brand or hoist model, so you're free to use whatever manual or powered hoist you have or need. Trolleys 5-ton capacity and under have A & B models adjustable to fit a wide range of beam widths and profiles. Trolleys are equipped with wrap around steel trolley guards which protect the trolley and also provide drop protection. Rubber Bumpers are available as optional equipment.

HTP PLAIN TROLLEY



HTG GEARED TROLLEY



CM	CM HTP & HTG CLEVIS TROLLEY	CBT TROLLEY	633 TROLLEY
CAPACITY RANGE	1/2 ton to 5 ton capacity upon initial launch. Additional capacities up to 20 ton coming soon!	1/4 ton to 5 ton capacity	1/2 ton to 5 ton capacity
INSTALLATION	Easy installation. No spacer washers required. Just rotate the threaded rod. Installation in seconds.	Uses spacer washers. Installation requires a longer set up and loose parts.	Uses spacer washers. Installation requires a longer set up and loose parts.
HEADROOM	Threaded rod with eyebolt suspension results in lower headroom compared to CBT & 633 trolleys. See tables on following page.	Standard Headroom	Standard Headroom
BEAM FLANGE RANGE	Trolleys are available in standard (A) models to fit beam flanges up to 8.67" and also wide flange (B) models to fit beam flanges up to 11.82". See tables on following page.	Standard models only. See tables on following page.	Standard models only. See tables on following page.
WEIGHT	Lower overall weight on most capacities vs. CBT & 633 Trolley contributes to the easy of installation. See tables on following page.	Higher overall weight than CM HTP/HTG trolley when comparing similar models & capacities. See tables on following page.	Higher overall weight than CM HTP/HTG trolley when comparing similar models & capacities. See tables on following page.

TECHNICAL DATA & DIMENSIONS

	CAPACITY (METRIC TONS)	FLANGE WIDTH (IN.)		THICKNESS (IN)	MIN RADIUS (IN)	WHEEL DIA. (IN.)	PLAIN TROLLEY WEIGHT (LBS.)	GEARED TROLLEY WEIGHT (LBS.)	
		MIN	MAX						
HTP/G TROLLEY	HTP/G 500A	1/2 ton	1.97	8.67	0.99	35.43	2.36	17.64	21.39
	HTP/G 1000A	1 ton	1.97	8.67	0.99	35.43	2.36	19.85	24.70
	HTP/G 2000A	2 ton	2.60	8.67	0.99	45.28	3.15	35.28	39.69
	HTP/G 3000A	3 ton	2.92	8.67	0.99	55.12	4.41	70.56	78.06
	HTP/G 5000A	5 ton	3.55	8.67	0.99	70.87	4.92	105.84	114.22
	HTP/G 500B	1/2 ton	6.30	11.82	1.58	35.43	2.36	23.37	27.78
	HTP/G 1000B	1 ton	6.30	11.82	1.58	35.43	2.36	26.46	31.09
	HTP/G 2000B	2 ton	6.30	11.82	1.58	45.28	3.15	42.56	46.97
	HTP/G 3000B	3 ton	6.30	11.82	1.58	55.12	4.41	78.94	86.44
	HTP/G 5000B	5 ton	7.09	11.82	1.58	70.87	4.92	115.10	123.48

CBT TROLLEY	CBTP0500	1/2 ton	2.00	8.70	N/A	27.00	2.36	19.00	N/A
	CBTP/G0100	1 ton	2.30	8.70	N/A	36.00	2.36	26.00	40.00
	CBTP/G0200	2 ton	2.30	8.70	N/A	45.00	3.15	46.00	60.00
	CBTP/G0300	3 ton	3.00	8.70	N/A	55.00	4.41	86.00	120.00
	CBTP/G0500	5 ton	3.50	8.70	N/A	70.00	4.92	130.00	148.00

633 TROLLEY	3302	1/2 ton	2.50	5.625	1.03	35.00	2.28	17.00	N/A
	3304	1 ton	3.00	8.00	1.03	35.00	3.47	36.00	N/A
	3306	2 ton	3.625	8.00	0.78	59.00	3.94	53.00	N/A
	3307	3 ton	4.00	8.00	1.19	71.00	5.13	100.00	N/A
	3309	5 ton	4.625	8.00	2.13	94.00	6.13	175.00	N/A



COLUMBUSMCKINNON.COM

USA: 800.888.0985 • 716.689.5400 • Fax: 716.689.5644

© 2020 Columbus McKinnon Corporation. All Rights Reserved.