

KNOCKOUT

TOOLS FOR SUCCESS

LODESTAR® D8+

The Lodestar D8+ meets all 2018 SQP2 requirements and is the only product on the market certified to meet this standard by TÜV SÜD. Made in the USA, the Lodestar D8+ ensures the highest level of safety for permanent applications and global tours. Designed to suspend loads without the need for secondary support, saving cost, time, and labor in rigging.

The clutch, outside the load path, acts as a precise overload device; and design factor is 8:1 with a double brake installed. The zinc plated or Black Phosphate Star Grade EN chain satisfies EN818-7 standards. The Lodestar D8+ comes in capacities 1/2T - 2T (500-2000 kg) (contact factory for higher capacities), speeds 8 to 64 feet/min, up to 184 feet of lift and available with 3 phase.



LODESTAR® D8+



LIFTKET



STAGEMAKER

CAPACITY	1/2T - 2T (500 - 2000 kg)	1/8T - 1-1/4T (125 - 1250 kg)	1/8T - 1-1/4T (125 - 1250 kg)
2018 SQP2 COMPLIANCE	TÜV SÜD 3rd Party Certified	Self Certified	Self Certified
WARRANTY	Lifetime	3 Years	2 Years
IP RATING	IP66	IP54	IP55
LOAD CELL INTEGRATION	Internal Integration Option	External as Option	External as Option
GEARBOX LUBRICATION	Grease Pack	Oil Pack	Oil Pack
MANUFACTURER LOCATION	Virginia, USA	Wurzen, Germany	Assembled in Ohio, US
CHAIN MANUFACTURER	Columbus McKinnon TN USA	Third Party	Third Party
WEIGHT (LESS CHAIN)	77 lbs (35 kg)	49 lbs (22 kg)	115 lbs (52 kg)
DIMENSIONS 1/2T (500 KG)	6.6 in (168 mm) x 20.6 in (522 mm) x 8.7 in (220 mm)	6.6 in (167 mm) x 13.8 in (350 mm) x 10.2 in (258 mm)	7.125 in (184 mm) x 21.4375 in (545 mm) x 15.9375 in (412 mm)